



Slip Check to AS 4586-2013

30x60 Concrete Project Nero Bocciardato (CONPROJ RB36N)

Report Number: R18644b Report Date: 17 May 2019 Total Number of Pages 2

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports

Issued by

Safe Environments Pty Ltd Unit 4, 40 Bessemer Street Blacktown NSW 2148

Prepared for

Trend Tile Pty Ltd 10 Roussell Road Eastern Creek NSW 2766 Approved by

Nasser Cura Authorised Signatory

Page 1 of 2 info@SafeEnvironments.com.au www.SafeEnvironments.com.au

17 May 2019 AS 4586-2013 Template Rev_6 R18644b - Slip Check, Project Nero Bocciardato





17 May 2019

Test Report No. R18644b

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix A (Wet Pendulum Test)

The slip resistance classification has been determined for unused surfaces using specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586 and HB 198.

Requested by: Client Address:	Trend Tile Pty Ltd 10 Roussell Road Eastern Creek NSW 2766				
Product Manufacturer:	Co-operativa Ceramica D'imola				
Product Description:	30x60 Concrete Project Nero Bocciardato (CONPROJ RB36N)				
Test conducted according to: Location: Conducted by:	AS 4586:2013 Appendix A 4/40 Bessemer Street, Blackt Kieran Mackowski	own NSW 2148			
Date:	16 May 2019	Temperature:	21°C		
Sample:	Unfixed	Cleaning:	None		
Rubber slider used:	Slider 96	Conditioned:	Grade P 400 paper dry followed		
Slope of specimen:	Tested on a flat level surface		by wet lapping film		
Direction of Test:	NA				

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	44	37	40	42	39

Reported SRV of Sample:	40
Class:	P3