





## Slip Check to AS 4586-2013 150x170 Timeless White Hexagonal Matte

Report Number: R23495c Report Date: 11 May 2021 Total Number of Pages 2

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports

Issued by

**Prepared for** 

Safe Environments Pty Ltd Unit 4, 40 Bessemer Street Blacktown NSW 2148 Trend Tile 10 Rousell Road Eastern Creek NSW 2766

Nasser Cura Authorised Signatory

Approved by

11 May 2021

## Test Report No. R23495c

## Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix A (Wet Pendulum Test)

The slip resistance classification has been determined for unused surfaces using specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 Guide to the specification and testing of slip resistance of pedestrian surfaces provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586 and HB 198.

Requested by: Trend Tile Client Address: 10 Rousell Road

Eastern Creek NSW 2766

Product Manufacturer:

Product Description: 150x170 Timeless White Hexagonal Matte

Test conducted according to: AS 4586:2013 Appendix A

4/40 Bessemer Street, Blacktown NSW 2148 Location:

Conducted by: Oshi Barkat

10 May 2021 Temperature: 22°C Date: Unfixed None Sample: Cleaning:

Slider 96 Rubber slider used: Conditioned: Grade P 400 paper dry followed

Slope of specimen: Tested on a flat level surface by wet lapping film

Direction of Test: N/A

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	54	54	52	51	51

Reported SRV of Sample:	52
Class:	P4

This test report shall not be reproduced unless in full, without written approval of Safe Environments Pty Ltd